

Superslim Cassette 840x840

PRODUCT SHEET



KID-02 S
Recommended controller




Product certified by:



FEATURES

Model	KCISC-140 DTN11
Cooling capacity	12,60 kW
Cooling power input	5.490 W
Heating capacity	12,89 kW
Heating power input	4.670 W
Airflow (indoor)	1.381/1.568/1.715 m³/h
Sound pressure (indoor)	49/50/52 dB(A)
Airflow (outdoor)	3.600 m³/h
Sound pressure (outdoor)	64 dB(A)
Power supply	380-415 V / 3 / 50 Hz
Max. input	13 A
Power wiring (indoor)	(2+T)x2,50 mm²
Power wiring (outdoor)	(4+T)x4 mm²
Communication wiring	2x1,50 mm²
Com. bus shielded	3x1,50 mm²

WIRING DIAGRAM




NOTES:

(1) The data and specifications present in this sheet may vary without notice.

(2) The images on this sheet are indicative and may be different from the final machine.


COOLING CONNECTION

Model	KCISC-140 DTN11
Refrigerating pipes	Ø3/8" / Ø5/8"
Refrigerant charge / Additional charge	4,30 kg / 0,03 kg
Indoor drain pipe	Ø25 mm
Max. pipe length (A)	65 m
Max. level difference (B)	30 m




DIMENSIONS & WEIGHT INDOOR

Model	KCIS-140 DR11
Width	840 mm
Height	287 mm
Depth	840 mm
Weight	29 kg





DIMENSIONS & WEIGHT OUTDOOR

Model	KUEC-140 DTN10
Width	1.394 mm
Height	568 mm
Depth	783 mm
Weight	177 kg



INSTALLATION



Superslim Cassette 840x840

PRODUCT SHEET



KID-02 S

Recommended controller




Product certified by:



FEATURES

Model	KCISC-160 DTN11
Cooling capacity	16,11 kW
Cooling power input	6.760 W
Heating capacity	16,99 kW
Heating power input	6.130 W
Airflow (indoor)	1.537/1.737/1.970 m³/h
Sound pressure (indoor)	48/50,50/53 dB(A)
Airflow (outdoor)	3.600 m³/h
Sound pressure (outdoor)	64 dB(A)
Power supply	380-415 V / 3 / 50 Hz
Max. input	15 A
Power wiring (indoor)	(2+T)x2,50 mm²
Power wiring (outdoor)	(4+T)x4 mm²
Communication wiring	2x1,50 mm²
Com. bus shielded	3x1,50 mm²

WIRING DIAGRAM




NOTES:

(1) The data and specifications present in this sheet may vary without notice.

(2) The images on this sheet are indicative and may be different from the final machine.


COOLING CONNECTION

Model	KCISC-160 DTN11
Refrigerating pipes	Ø3/8" / Ø5/8"
Refrigerant charge / Additional charge	4,30 kg / 0,03 kg
Indoor drain pipe	Ø25 mm
Max. pipe length (A)	65 m
Max. level difference (B)	30 m




DIMENSIONS & WEIGHT INDOOR

Model	KCIS-160 DR11
Width	840 mm
Height	287 mm
Depth	840 mm
Weight	29,70 kg



DIMENSIONS & WEIGHT OUTDOOR

Model	KUEC-160 DTN10
Width	1.394 mm
Height	568 mm
Depth	783 mm
Weight	177 kg



INSTALLATION

