



ENERG
енергия · ενέργεια

Y IJA
IE IA



KEM-12 DVR



55°C

35°C

A+++

A++

A+

A


B

C

D

A++

A+++




-- dB

11 12


12 12

12 12

kW kW



70dB



2019

811/2013

Mini Inverter heat pump space heating		Outdoor	KEM-12 DVR
Outdoor unit sound power ()	Average climate low temperature application	dB	70
	Average climate medium temperature application	dB	70
Space heating	Energy efficiency class 35°C (Low temp. app.)	-	A+++
Space heating	Energy efficiency class 55°C (Medium temp. app.)	-	A++
Average climate (Design temperature = -10°C)			
Space heating 35°C	Prated (declared heating capacity) @ -10°C	[kW]	12.3
	Seasonal space heating efficiency (ηs)	[%]	200.1
	Annual energy consumption	[kWh]	5,004
Space heating 55°C	Prated (declared heating capacity) @ -10°C	[kW]	12.5
	Seasonal space heating efficiency (ηs)	[%]	141.6
	Annual energy consumption	[kWh]	7,148
Part load conditions space heating average climate low temperature application			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	10.85
	COPd (declared COP)	-	3.11
	Cdh(degradation coefficient)	-	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.79
	COPd (declared COP)	-	4.86
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.79
	COPd (declared COP)	-	6.98
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.73
	COPd (declared COP)	-	9.02
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-10.00
	Pdh (declared heating capacity)	[kW]	12.30
	COPd (declared COP)	-	2.80
	WTOL (Heating water Operation Limit)	[°C]	65

Temperature application

Model	For medium - temperature application										
	Energy efficiency class	Unit sound power	average climate			colder climate			warmer climate		
			Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption
-	dB	kW	%	kWh	kW	%	kWh	kW	%	kWh	
KEM-12 DVR	A++	70	12.5	141.6	7148	11.3	126.0	8628	12.0	179.0	3524

Model	For low - temperature application										
	Energy efficiency class	Unit sound power	average climate			colder climate			warmer climate		
			Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption	Rated heat output	Seasonal space heating energy efficiency	For space heating annual energy consumption
-	dB	kW	%	kWh	kW	%	kWh	kW	%	kWh	
KEM-12 DVR	A+++	70	12.3	200.1	5004	12.5	168.8	7153	12.1	262.3	2437

Mini Inverter heat pump space heating		Outdoor	KEM-12 DVR
(F) Tivalent temperature	Tbiv	[°C]	-7.00
	Pdh (declared heating capacity)	[kW]	10.85
	COPd (declared COP)	-	3.11
Supplementary capacity at P_design	Psup (@Tdesignh: -10°C)	[kW]	0.00
Part load conditions space heating average climate medium temperature application			
(A) condition (-7°C)	Pdh (declared heating capacity)	[kW]	11.06
	COPd (declared COP)	-	2.15
	Cdh(degradation coefficient)	-	0.90
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	6.91
	COPd (declared COP)	-	3.59
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	4.64
	COPd (declared COP)	-	5.07
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	2.15
	COPd (declared COP)	-	4.52
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	-10.00
	Pdh (declared heating capacity)	[kW]	10.97
	COPd (declared COP)	-	1.98
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tivalent temperature	Tbiv	[°C]	-7.00
	Pdh (declared heating capacity)	[kW]	11.06
	COPd (declared COP)	-	2.15
Supplementary capacity at P_design	Psup (@Tdesignh: -10°C)	[kW]	1.53
Colder climate (Design temperature = -22°C)			
Space heating 35°C	Prated (declared heating capacity) @ -22°C	[kW]	12.5
	Seasonal space heating efficiency (ηs)	[%]	168.8
	Annual energy consumption	[kWh]	7,153

Mini Inverter heat pump space heating		U [~] cá[[]	SÒT ÈGÒXÜ
Ú] æÁ@æþ * ÁÍ »Ô	Ú! æ^á/Á^æ^á/Á@æþ * Áææ æææ D Æ Á GÖÖ	Ž Y á	FFÈH
	Ú^æ [] æ^Á æÁ@æþ * Á-ææ } & ÁÇ • D	Ž Á á	FG ÈÈ
	Ç } ^ æ^Á) ^! * ^ Á } • ^ {] Ç }	Ž Y Ç	ì È G
Úæó[æÁ/æ] áæþ } • Á] æÁ@æþ * Á/ á^/Á/æ æÁ[, Á^ {] ^!æ^!^Á } ææþ }			
ÇÈ& [] áæþ } ÁÈ »ÔD	Úá ÇÁ^æ^á/Á@æþ * Áææ æææ D	Ž Y á	ì ÈÈ
	ÔUÚá/Á^æ^á/Á@æþ * Áææ æææ D	È	HÈ I
	Óá ÇÁ^!ææþ } Á/ ^-ææ } d	È	€€€
ÇÐ& [] áæþ } ÁÇ »ÔD	Úá ÇÁ^æ^á/Á@æþ * Áææ æææ D	Ž Y á	I ÈH
	ÔUÚá/Á^æ^á/Á@æþ * Áææ æææ D	È	ì ÈH
	Óá ÇÁ^!ææþ } Á/ ^-ææ } d	È	€€€
ÇÒ& [] áæþ } ÁÇ »ÔD	Úá ÇÁ^æ^á/Á@æþ * Áææ æææ D	Ž Y á	HÈ Ì
	ÔUÚá/Á^æ^á/Á@æþ * Áææ æææ D	È	ì ÈÈ
	Óá ÇÁ^!ææþ } Á/ ^-ææ } d	È	€€€
ÇÒ& [] áæþ } ÁÇ »ÔD	Úá ÇÁ^æ^á/Á@æþ * Áææ æææ D	Ž Y á	HÈ J
	ÔUÚá/Á^æ^á/Á@æþ * Áææ æææ D	È	J ÈH
	Óá ÇÁ^!ææþ } Á/ ^-ææ } d	È	€€€
ÇÒV [] Á^æ^!^Á] ^!ææ * Áæ æD	V [Á^æ^!^Á] ^!ææ * Áæ æD	Ž Óá	ÈÇÈ€€
	Úá ÇÁ^æ^á/Á@æþ * Áææ æææ D	Ž Y á	ì È G
	ÔUÚá/Á^æ^á/Á@æþ * Áææ æææ D	È	ÇÈÈ
	Y VUŠÁ^ææ * Á æÁ/Á] ^!ææ } Áæ æD	Ž Óá	ì Ì
ÇÒVáææ^) ó^ [] ^!æ^!^	Váæ	Ž Óá	È Ì È€€
	Úá ÇÁ^æ^á/Á@æþ * Áææ æææ D	Ž Y á	FÈÈ Ì
	ÔUÚá/Á^æ^á/Á@æþ * Áææ æææ D	È	ÇÈ Ì
Ú^]] ^ (^) ææ æææ æææ^ á^ • æ }	Ú^] ÁÇ Vá^ • æ } Ç Á GÖÖ	Ž Y á	HÈ Ì
Úæó[æÁ/æ] áæþ } • Á] æÁ@æþ * Á/ á^/Á/æ æÁ[^ áæ { Á^ {] ^!æ^!^Á } ææþ }			
ÇÈ& [] áæþ } ÁÈ »ÔD	Úá ÇÁ^æ^á/Á@æþ * Áææ æææ D	Ž Y á	ì ÈÈ
	ÔUÚá/Á^æ^á/Á@æþ * Áææ æææ D	È	ÇÈ Ì
	Óá ÇÁ^!ææþ } Á/ ^-ææ } d	È	€€€

Mini Inverter heat pump space heating		Outdoor	KEM-12 DVR
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	4.44
	COPd (declared COP)	-	3.88
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	3.00
	COPd (declared COP)	-	4.88
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.60
	COPd (declared COP)	-	6.61
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating lim	Tol (temperature operating limit)	[°C]	-22.00
	Pdh (declared heating capacity)(E) Tol (temperature operating lim	[kW]	7.00
	COPd (declared COP)	-	1.38
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tivalent temperature	Tbiv	[°C]	-15.00
	Pdh (declared heating capacity)	[kW]	9.21
	COPd (declared COP)	-	1.92
Supplementary capacity at P_design	Psup (@Tdesignh: -22°C)	[kW]	4.30
Warmer climate (Design temperature = 2°C)			
Space heating 35°C	Prated (declared heating capacity) @ 2°C	[kW]	12.1
	Seasonal space heating efficiency (ηs)	[%]	262.3
	Annual energy consumption	[kWh]	2,437
Space heating 55°C	Prated (declared heating capacity) @ 2°C	[kW]	12.0
	Seasonal space heating efficiency (ηs)	[%]	179.0
	Annual energy consumption	[kWh]	3,524
Part load conditions space heating warmer climate low temperature application			
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	12.10
	COPd (declared COP)	-	3.53
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	7.78
	COPd (declared COP)	-	5.82
	Cdh(degradation coefficient)	-	0.90

Mini Inverter heat pump space heating		Outdoor	KEM-12 DVR
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.64
	COPd (declared COP)	-	8.31
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	2.00
	Pdh (declared heating capacity)	[kW]	12.10
	COPd (declared COP)	-	3.53
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tbivalent temperature	Tbiv	[°C]	7.00
	Pdh (declared heating capacity)	[kW]	7.78
	COPd (declared COP)	-	5.82
Supplementary capacity at P_design	Psup (@Tdesignh: 2°C)	[kW]	0.00
Part load conditions space heating warmer climate medium temperature application			
(B) condition (2°C)	Pdh (declared heating capacity)	[kW]	12.00
	COPd (declared COP)	-	2.39
	Cdh(degradation coefficient)	-	0.90
(C) condition (7°C)	Pdh (declared heating capacity)	[kW]	7.73
	COPd (declared COP)	-	3.86
	Cdh(degradation coefficient)	-	0.90
(D) condition (12°C)	Pdh (declared heating capacity)	[kW]	3.59
	COPd (declared COP)	-	5.88
	Cdh(degradation coefficient)	-	0.90
(E) Tol (temperature operating limit)	Tol (temperature operating limit)	[°C]	2.00
	Pdh (declared heating capacity)	[kW]	12.00
	COPd (declared COP)	-	2.39
	WTOL (Heating water Operation Limit)	[°C]	65
(F) Tbivalent temperature	Tbiv	[°C]	7.00
	Pdh (declared heating capacity)	[kW]	7.73
	COPd (declared COP)	-	3.86
Supplementary capacity at P_design	Psup (@Tdesignh: 2°C)	[kW]	0.00

Mini Inverter heat pump space heating		Outdoor	KEM-12 DVR
Product description	Air-to-water heat pump	Y/N	Yes
	Water-to-water heat pump	Y/N	No
	Brine-to-water heat pump	Y/N	No
	Low-temperature heat pump	Y/N	No
	Equipped with a supplementary heater	Y/N	Yes
	Heat pump combination heater	Y/N	Yes
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	5200
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	-	/
Other	Capacity control	-	Inverter
	Poff (Power consumption Off mode)	[kW]	0.013
	Pto (Power consumption Thermostat off mode)	[kW]	0.020
	Psb (Power consumption Standby mode)	[kW]	0.013
	Pck (Power crankcase heater model)	[kW]	0.000
	Qelec (Daily electricity consumption)	[kWh]	/
	Qfuel (Daily fuel consumption)	[kWh]	/
<p>Note :</p> <p>Product fiche data according to energy label directive 2010/30/EC regulation (EU) 811/2013.</p> <p>Sound power measured according to the EN12102 under conditions of the EN14825.</p> <p>Details and precautions on installation, maintenance and assembly can be found in the installation and or operation manuals.</p>			

Mini Inverter heat pump space cooling		Outdoor	KEM-12 DVR
Outdoor unit sound power (*)	Average climate low temperature application	dB	69
	Average climate medium temperature application	dB	69
Space cooling 7°C	Prated (declared cooling capacity) @ 35°C	[kW]	11.7
	Seasonal space cooling efficiency (ηs)	[%]	199.92
	Annual energy consumption	[kWh]	1,380
Space cooling 18°C	Prated (declared cooling capacity) @ 35°C	[kW]	12.1
	Seasonal space cooling efficiency (ηs)	[%]	308.53
	Annual energy consumption	[kWh]	932
Part load conditions space cooling : low temperature application@7°C			
(A) condition (35°C)	Pdc (declared cooling capacity)	[kW]	11.67
	EERd (declared EER)	-	3.11
	Cdc(degradation coefficient)	-	0.90
(B) condition (30°C)	Pdc (declared cooling capacity)	[kW]	8.84
	EERd (declared EER)	-	4.14
	Cdc(degradation coefficient)	-	0.90
(C) condition (25°C)	Pdc (declared cooling capacity)	[kW]	5.64
	EERd (declared EER)	-	5.71
	Cdc(degradation coefficient)	-	0.90
(D) condition (20°C)	Pdc (declared cooling capacity)	[kW]	2.75
	EERd (declared EER)	-	6.76
	Cdc(degradation coefficient)	-	0.90

Mini Inverter heat pump space cooling		Outdoor	KEM-12 DVR
Part load conditions space cooling : medium temperature application@18°C			
(A) condition (35°C)	Pdc (declared cooling capacity)	[kW]	12.10
	EERd (declared EER)	-	4.77
	Cdc(degradation coefficient)	-	0.90
(B) condition (30°C)	Pdc (declared cooling capacity)	[kW]	9.24
	EERd (declared EER)	-	6.67
	Cdc(degradation coefficient)	-	0.90
(C) condition (25°C)	Pdc (declared cooling capacity)	[kW]	5.83
	EERd (declared EER)	-	9.38
	Cdc(degradation coefficient)	-	0.90
(D) condition (20°C)	Pdc (declared cooling capacity)	[kW]	3.86
	EERd (declared EER)	-	9.38
	Cdc(degradation coefficient)	-	0.90
Air to water unit	Rated airflow (outdoor)	[m ³ /h]	5200
Brine/water to water unit	Rated water/brine flow (outdoor H/E)	-	/
Other	Capacity control	-	Inverter
	Poff (Power consumption Off mode)	[kW]	0.013
	Pto (Power consumption Thermostat off mode)	[kW]	0.005
	Psb (Power consumption Standby mode)	[kW]	0.013
	Pck (Power crankcase heater mode)	[kW]	0.000
	Qelec (Daily electricity consumption)	[kWh]	/
	Qfuel (Daily fuel consumption)	[kWh]	/

Outdoor unit	Ambient Temperature: 35/24 Water temperature: 23/18			Ambient Temperature: 35/24 Water temperature: 12/7			Ambient Temperature: 7/6 Water temperature: 30/35			Ambient Temperature: 2/1 Water temperature: 30/35		
	Capacity kW	Power input kW	EER	Capacity kW	Power input kW	EER	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
KEM-12 DVR	12.20	2.652	4.60	11.60	3.742	3.10	12.20	2.490	4.90	12.30	3.417	3.60

Outdoor unit	Ambient Temperature: -7/-8 Water temperature: 30/35			Ambient Temperature: 7/6 Water temperature: 40/45			Ambient Temperature: 2/1 Water temperature: 40/45			Ambient Temperature: -7/-8 Water temperature: 40/45		
	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
KEM-12 DVR	11.60	4.070	2.85	12.50	3.378	3.70	12.00	4.138	2.90	11.50	4.792	2.40

Outdoor unit	Ambient Temperature: 7/6 Water temperature: 47/55			Ambient Temperature: 2/1 Water temperature: 47/55			Ambient Temperature: -7/-8 Water temperature: 47/55		
	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP	Capacity kW	Power input kW	COP
KEM-12 DVR	12.00	4.000	3.00	12.00	5.106	2.35	10.80	5.143	2.10