

Multi Hybrid HR Multisystem

PRODUCT SHEET


Product certified by:



FEATURES

Model	KTHR-190
Heating capacity ¹	3,90 kW
COP ¹	3,4
Recovery time ¹	2h 30 min
Tank volume	190L
Weight	70 kg
Support resistance	2 kW
Tank	Enameled steel
Corrosion protection	Magnesium anode
Heat exchanger	Microchannel
Communication wiring	(3+T)x1 mm
Refrigeration piping	Ø1/4" / Ø3/8"
Hydraulic connections	Ø3/4" (DN20)
Drain connections	Ø3/4" (DN20)
Water outlet temperature range	38°C - 70°C (up to +70°C during disinfection with electrical resistance)

WIRING DIAGRAM



NOTES:

(1) The data and specifications present in this sheet may vary without notice.

(2) The images on this sheet are indicative and may be different from the final machine.

REFRIGERATING PIPING

Model	KTHR-190
Diam. liquid / gas pipes	4xØ1/4" / 3xØ3/8" + 1xØ1/2"
Max. length for all rooms	80 m
Max. length for 1 indoor unit / tank	35 m / 20 m
Max. height difference between indoor and outdoor unit	15 m
Max. height difference between indoor units	10 m

DIMENSIONS & WEIGHT INDOOR

Model	KTHR-190
Width	504 mm
Height	1660 mm
Depth	574 mm