

Aquantia KHP-MO HT HP



KCTAQ-03
Standard

Technical documentation	Download
Technical Manual	PDF
User Manual	PDF
Controller Manual	PDF
Declaration of Conformity	PDF
ErP	PDF
Installation diagrams	PDF



Basic modules

Set model		KHP-MO 26 DTP	KHP-MO 30 DTP	KHP-MO 35 DTP	KHP-MO 40 DTP
> Set					
Heating capacity / COP (A+7°C / W+35°C)	kW	26.0 / 4.77	30.0 / 4.5	35.0 / 4.17	39.0 / 4.0
Consumption (A+7 °C / W+35 °C)	W	5450	6670	8400	9750
Heating capacity / COP (A+7°C / W+55°C)	kW	26 / 3.31	30.0 / 3.13	35.0 / 2.98	39.0 / 2.34
Consumption (A+7 °C / W+55 °C)	W	7850	9570	11750	14000
Heating capacity / COP (A-7°C / W+35°C)	kW	21 / 3.03	24.0 / 2.86	28.2 / 2.54	28.2 / 2.54
Consumption (A-7 °C / W+35 °C)	W	6930	8380	11100	11100
Heating capacity / COP (A-7°C / W+55°C)	kW	18.8 / 2.30	21.3 / 2.22	24.8 / 2.08	24.8 / 2.08
Consumption (A-7 °C / W+55 °C)	W	8170	9600	11900	11900
Cooling capacity / EER (A+35°C / W+18°C)	kW	26.0 / 4.64	30.0 / 4.41	35.0 / 4.12	39.0 / 3.96
Consumption (A+35 °C / W+18 °C)	W	5600	6800	8500	9850
Cooling capacity / EER (A+35°C / W+7°C)	kW	26.0 / 3.10	30.0 / 2.80	32.0 / 2.67	32.0 / 2.67
Consumption (A+35 °C / W+7 °C)	W	8400	10700	11980	11980
Average heating climate (W+35°C / W+55°C). Energy class		A+++ / A+++	A+++ / A++	A+++ / A++	A++ / A++
Average heating climate (W+35°C / W+55°C). η _s	%	194.9 / 150.7	193.8 / 148.7	176.3 / 142.4	176.3 / 142.4
Average heating climate (W+35°C / W+55°C). SCOP		4.95 / 3.84	4.98 / 3.79	4.48 / 3.63	3.84 / 3.00
Warm heating climate (W+35°C / W+55°C). η _s	%	259.80 / 194.80	247.5 / 193.1	240.3 / 187.1	240.3 / 187.1
Warm heating climate (W+35°C / W+55°C). SCOP		6.57 / 4.94	6.26 / 4.90	6.08 / 4.75	5.35 / 4.50
Cold heating climate (W+35°C / W+55°C). η _s	%	155 / 126	153 / 123	151 / 118	151 / 118
Cold heating climate (W+35°C / W+55°C). SCOP		3.95 / 3.23	3.91 / 3.14	3.85 / 3.03	4.32 / 3.47
Chilling efficiency (W+7°C / W+18°C). Keymark certification. SEER		5.21 / 7.17	4.99 / 6.8	4.82 / 6.43	4.82 / 6.22
Width / Height / Depth	mm	1384 / 1816 / 523	1384 / 1816 / 523	1384 / 1816 / 523	1384 / 1816 / 523
Net weight	kg	245	245	245	245
Power supply	V/ph/Hz	380-415 / 3 / 50	380-415 / 3 / 50	380-415 / 3 / 50	380-415 / 3 / 50
Max. intensity	A	32	32	32	32
Circuit breaker	A		D45	D45	D45
Communication wiring	mm ²	2x1	2x1	2x1	2x1
Wiring to controller	mm ²	2x1,5	2x1,5	2x1,5	2x1,5
Sound pressure	dB(A)	55	61.3	75.6	77
Sound power	dB(A)	69	74	75	76
Type of refrigerant		R-290	R-290	R-290	R-290
GWP		3	3	3	3
Refrigerant charge	kg	2.9	2.9	2.9	2.9
t CO ₂ eq	tCO ₂	0.008	0.008	0.008	0.008
Minimum water volume	l	130	150	175	200
Nominal flow rate	m ³ /h	5.1	5.1	6.0	6.0
Electrical heater support	W	Not included	Not included	Not included	Not included
Water pump pressure	mH ₂ O	12	12	12	12
Expansion vessel	l	5	5	5	5
Water pipe connections	inch	1 1/4"	1 1/4"	1 1/4"	1 1/4"

Aquantia KHP-MO HT HP

Basic modules

Set model	KHP-MO 26 DTP	KHP-MO 30 DTP	KHP-MO 35 DTP	KHP-MO 40 DTP
> Working range				
Outdoor ambient temperature for DHW min. / max. °C	-25 / 43	-25 / 43	-25 / 43	-25 / 43
Outdoor ambient temperature for heating min. / max. °C	-25 / 35	-25 / 35	-25 / 35	-25 / 35
Outdoor ambient temperature for cooling min. / max. °C	-15 / 48	-15 / 48	-15 / 48	-15 / 48
Leaving water temperature; min. / max. DHW °C	20 / 70	20 / 70	20 / 70	20 / 70
Leaving water temperature; min. / max. heating °C	25 / 85	25 / 85	25 / 85	25 / 85
Leaving water temperature; min. / max. cooling °C	5 / 30	5 / 30	5 / 30	5 / 30

Cooling capacity. Cooling input. EER: Data calculated in compliance with EN 14511:2018 Standard, with reference to the following conditions: indoor heat exchanger water temperature = 12/7°C; outdoor heat exchanger inlet air temperature = 35°C.

Heating capacity. Heating input. COP: Data calculated in compliance with EN 14511:2018 Standard, with reference to the following conditions: indoor heat exchanger water temperature = 40/45°C; outdoor heat exchanger inlet air temperature = 7°C DB/6°C WB.

SEER. SCOP: Data calculated in compliance with EN 14825:2016 Standard. The product meets the ErP (Energy Related Products) European Directive, which include the (EU) Commission Delegated Regulation No. 811/2013 (rated thermal input ≤ 70 kW under specified reference conditions) and (EU) Commission Delegated Regulation No. 813/2013 (rated thermal input ≤ 400 kW under specified reference conditions).

Sound pressure: Sound levels refer to the unit under full charge. The sound pressure level refers to the measurement taken at a distance of 1 m from the external surface of the unit, operating in the open air. The measurements are taken in accordance with UNI EN ISO 9614-2 standard, respecting the conditions imposed by EUROVENT 8/1 certification. Data under the following conditions: indoor heat exchanger water temperature = 12/7°C; outdoor air temperature = 35°C.

PRELIMINARY DATA

