

Cooling mode:

24HP

Heating mode:

Information requirements for heat pumps								
Model(s):K2F-670 DN6								
Test matching indoor units form, cassette: KCIBF-80 DN5.0×5+KCIBF-100 DN5.0×3								
Outdoor side heat exchanger of air conditioner: air								
Indoor side heat exchanger of air conditioner: air								
If the heater is equipped with a supplementary heater: no								
Driver of compressor: electric motor								
Parameters shall be declared for the average heating season, parameters for the warmer and colder heating seasons are optional.								
Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated heating capacity	P _{rated,h}	67.00	kW		Seasonal space heating energy efficiency	η _{s,h}	160.2	%
Declared heating capacity for part load at indoor temperature 20°C and outdoor temperatures T _j					Declared coefficient of performance or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures T _j			
T _j =-7°C	P _{dh}	32.16	kW		T _j =-7°C	COP _d	242	%
T _j =+2°C	P _{dh}	20.58	kW		T _j =+2°C	COP _d	395	%
T _j =+7°C	P _{dh}	12.46	kW		T _j =+7°C	COP _d	588	%
T _j =+12°C	P _{dh}	8.15	kW		T _j =+12°C	COP _d	666	%
T _{biv} =bivalent temperature	P _{dh}	36.85	kW		T _{biv} =bivalent temperature	COP _d	193	%
T _{OL} =operation temperature	P _{dh}	36.85	kW		T _{OL} =operation temperature	COP _d	193	%
Bivalent temperature	T _{biv}	-10	°C					
Degradation co-efficient for heat pumps(**)	C _{dh}	0.25	--					
Power consumption in modes other than "active mode"					Supplementary heater			
Off mode	P _{OFF}	0.005	kW		Back-up heating capacity(*)	elbu	0	kW
Thermostat-off mode	P _{TO}	0.005	kW		Type of energy input			
Crankcase heater mode	P _{CK}	0.05	kW		Standby mode	P _{SB}	0.05	kW
Other items								
Capacity control	variable				For air-to-air heat pump: air flow rate, outdoor measured	--	21500	m ³ /h
Sound power level,outdoor	LWA	92	dB					
GWP of the refrigerant		2088	kg CO ₂ eq (100years)					
Contact details								
(*)								
(**)If C _{dh} is not determined by measurement, then the default degradation coefficient of heat pumps shall be 0.25.								
Where information relates to multi-split heat pumps, the test result and performance data may be obtained on the basis of performance of the outdoor unit, with a combination of indoor unit(s) recommended by the manufacturer or importer.								